



Certificate number: 2308729 (1)

Issued 09/08/2023

Expires 09/08/2028

## Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

### Fortune Brands Water Innovations LLC.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

**Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.**

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory  
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec  
(A Trading Division of Kiwa Ltd)  
26A Rassau Industrial Estate  
Ebbw Vale  
Gwent  
NP23 5SD  
United Kingdom  
T +44 (0)1495 308185  
[uk.water@kiwa.com](mailto:uk.water@kiwa.com)  
[www.kiwa.co.uk](http://www.kiwa.co.uk)

**Certificate Issued to:**  
Fortune Brands Water Innovations LLC  
Al Moen Drive 25300  
NORTH OLMSTED  
OH 44070  
United States



KUKreg4

# Product Certificate

Appendix to Certificate number: 2308729

---

The following products belong to this certificate

<b>PRODUCT DESCRIPTION</b> Range of three-hole single outlet with brass bodies and various finishes. Products incorporate a ceramic disc headwork and aerator at the inlets. ATS3 – Without Production Surveillance.
<b>MODEL(S)</b> VY08C-EM bath faucet, chrome PX08C-EM bath faucet, chrome PX08BK-EM bath faucet, black PB08C-EM bath faucet, chrome PB08BK-EM bath faucet, black
<b>SIZE:</b> Flexible hose inlet arrangement.
<b>SCOPE:</b> Manufacturer recommended maximum working pressure 5 Bar & maximum operating temperature 60°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 60°C.
<b>MARKING</b> Riobel mark on body.
<b>MATERIALS</b> Non-metallic materials assessed (BS6920) to point of discharge.
<b>BACKFLOW PROTECTION NOTES</b> Consider balanced supplies or appropriate backflow protection at the inlets.
<b>ADDITIONAL NOTES</b> Opacity cannot be guaranteed at inlet hoses.

## Extra Notes