



Product certificate K0212980/01

Issued 2023-09-18

Replaces -

Page 1 of 2

Sanitary Tapware; thermostatic mixers

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Fortune Brands Water Innovations

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline **BRL-K610** "Sanitary tapware; Thermostatic mixers".

which includes the requirements of

EN 1111:2017 "Sanitary tapware - thermostatic mixing valves (PN10)"

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

CERTIFICATE

288171015

Kiwa Nederland B.V.

Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
NL.Kiwa.info@Kiwa.com
www.kiwa.nl

Company

Fortune Brands Water Innovations
Al Moen Drive 25300
OH 44070 NORTH OLMSTED
United States of America
Tel. +1 440-962-2903
olivia.caracostea@fbgpg.com
www.fbin.com

Certification process
consists of initial and
regular assessment of:

- quality system
- product



Sanitary Tapware; thermostatic mixers

TECHNICAL SPECIFICATION

Article number	Type	Cartridge
TGS23***-EM	Concealed shower mixing valve	0-924-EM-1
TGS44***-EM	Concealed shower mixing valve	0-914-EM-1
TPXTQ23***-EM	Concealed shower mixing valve	0-925-EM-1
TPXTQ44***-EM	Concealed shower mixing valve	0-915-EM-1
TVY23***-EM	Concealed shower mixing valve	0-924-EM-1
TVY44***-EM	Concealed shower mixing valve	0-914-EM-1
TPB23***-EM	Concealed shower mixing valve	0-924-EM-1
TPB44***-EM	Concealed shower mixing valve	0-914-EM-1

*** = colour code BK (Black) or C (Chrome)

FITNESS FOR CONTACT WITH DRINKING WATER

The specified products were not yet assessed for compliance with the requirements for hygienic aspects set in the “Regeling materialen en chemicaliën drink- en warm tapwatervoorziening” (Materials and chemicals in the supply of drinking water and warm tap water regulation”, dated 01-07-2017; published in the Dutch Government Gazette).

APPLICATION AND USE

Thermostatic mixing valves are intended for application in tap water installations with a static working pressure of maximum 1000 kPa and a maximum water temperature of 90°C. The recommended limits for correct operation are a working pressure of 100 kPa up to 500 kPa and a water temperature of maximum 65°C.

MARKING

The Kiwa®-mark products are marked with the wordmark “KIWA”.

Place of the mark: on the body.

Compulsory specifications:

- name or mark of the manufacturer “Riobel”: on the body;
- indication of the acoustic group, if classified: on the body;
- indication of the flow rate class, if classified: on the body.

Method of marking:

- non-erasable;
- visible after assembly.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Fortune Brands Water Innovations
and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.